



■ Applications:

Used where extensive vibration is there & positive locking is required.

■ **Material:** Stainless Steel SS 316, SS 304

■ **Operating Temp:** -80°C to +150°C

■ **Unit:** 100 Pcs/Pkt

Features:

- Modified wave form clamps where no other steel ties retain tension
- Grips firmly on solid object at low applied forces
- Coating material is non-toxic, halogen free, low smoke and UV resistant with long term life in corrosive climate

Length (mm)	Width (mm)	Thick (mm)	Max. Bun. Dia (mm)	Length (inch)	Width (inch)	Coating Type	Loop Ten. Str.		G.W. /100 pcs Kgs (lbs)	Cat No. SS 316	Cat No. SS 304
							Kgs	(Lbs)			
200	4.6	0.38	50	7.87	0.18	POLYESTER	60	(132)	0.27 (0.60)	BLZ-200CP	BLZ-200/4CP
200	4.6	0.45	50	7.87	0.18	NYLON	40	(88)	0.27 (0.60)	BLZ-200CN	BLZ-200/4CN
360	4.6	0.38	100	14.17	0.18	POLYESTER	60	(132)	0.43 (0.95)	BLZ-360CP	BLZ-360/4CP
360	4.6	0.45	100	14.17	0.18	NYLON	40	(88)	0.43 (0.95)	BLZ-360CN	BLZ-360/4CN
520	4.6	0.38	150	20.47	0.18	POLYESTER	60	(132)	0.58 (1.29)	BLZ-520CP	BLZ-520/4CP
520	4.6	0.45	150	20.47	0.18	NYLON	40	(88)	0.58 (1.29)	BLZ-520CN	BLZ-520/4CN
680	4.6	0.38	200	26.77	0.18	POLYESTER	60	(132)	0.74 (1.64)	BLZ-680CP	BLZ-680/4CP
680	4.6	0.45	200	26.77	0.18	NYLON	40	(88)	0.74 (1.64)	BLZ-680CN	BLZ-680/4CN
840	4.6	0.38	250	33.07	0.18	POLYESTER	60	(132)	0.90 (1.99)	BLZ-840CP	BLZ-840/4CP
840	4.6	0.45	250	33.07	0.18	NYLON	40	(88)	0.90 (1.99)	BLZ-840CN	BLZ-840/4CN
1000	4.6	0.38	300	39.37	0.18	POLYESTER	60	(132)	1.06 (2.33)	BLZ-1000CP	BLZ-1000/4CP
1000	4.6	0.45	300	39.37	0.18	NYLON	40	(88)	1.06 (2.33)	BLZ-1000CN	BLZ-1000/4CN
200	7.9	0.38	50	7.87	0.31	POLYESTER	170	(375)	0.51 (1.12)	BLHZ-200CP	BLHZ-200/4CP
200	7.9	0.45	50	7.87	0.31	NYLON	80	(176)	0.51 (1.12)	BLHZ-200CN	BLHZ-200/4CN
360	7.9	0.38	100	14.17	0.31	POLYESTER	170	(375)	0.78 (1.72)	BLHZ-360CP	BLHZ-360/4CP
360	7.9	0.45	100	14.17	0.31	NYLON	80	(176)	0.78 (1.72)	BLHZ-360CN	BLHZ-360/4CN
520	7.9	0.38	150	20.47	0.31	POLYESTER	170	(375)	1.05 (2.31)	BLHZ-520CP	BLHZ-520/4CP
520	7.9	0.45	150	20.47	0.31	NYLON	80	(176)	1.05 (2.31)	BLHZ-520CN	BLHZ-520/4CN
680	7.9	0.38	200	26.77	0.31	POLYESTER	170	(375)	1.32 (2.91)	BLHZ-680CP	BLHZ-680/4CP
680	7.9	0.45	200	26.77	0.31	NYLON	80	(176)	1.32 (2.91)	BLHZ-680CN	BLHZ-680/4CN
840	7.9	0.38	250	33.07	0.31	POLYESTER	170	(375)	1.59 (3.51)	BLHZ-840CP	BLHZ-840/4CP
840	7.9	0.45	250	33.07	0.31	NYLON	80	(176)	1.59 (3.51)	BLHZ-840CN	BLHZ-840/4CN
1000	7.9	0.38	300	39.37	0.31	POLYESTER	170	(375)	1.86 (4.10)	BLHZ-1000CP	BLHZ-1000/4CP
1000	7.9	0.45	300	39.37	0.31	NYLON	80	(176)	1.86 (4.10)	BLHZ-1000CN	BLHZ-1000/4CN