



Applications:

Used where extensive vibration is there & positive locking is required.

■ **Material:** Stainless Steel SS 316, SS 304

■ **Operating Temp:** -80°C to +538°C

■ **Unit:** 100 Pcs/Pkt

Features:

- Modified wave form clamps where no other steel ties retain tension
- Grips firmly on solid object at low applied forces
- Smooth edges of ties provide utmost safety while installation

| Length (mm) | Width (mm) | Thick (mm) | Max. Bun. Dia (mm) | Length (inch) | Width (inch) | Loop Ten. Str. | | G.W. /100 pcs Kgs (lbs) | Cat No. SS 316 | Cat No. SS 304 |
|-------------|------------|------------|--------------------|---------------|--------------|----------------|-------|-------------------------|----------------|----------------|
| | | | | | | Kgs | (Lbs) | | | |
| 200 | 4.6 | 0.25 | 50 | 7.87 | 0.18 | 60 (132) | | 0.25 (0.56) | BLZ-200 | BLZ-200/4 |
| 360 | 4.6 | 0.25 | 100 | 14.17 | 0.18 | 60 (132) | | 0.40 (0.88) | BLZ-360 | BLZ-360/4 |
| 520 | 4.6 | 0.25 | 150 | 20.47 | 0.18 | 60 (132) | | 0.55 (1.21) | BLZ-520 | BLZ-520/4 |
| 680 | 4.6 | 0.25 | 200 | 26.77 | 0.18 | 60 (132) | | 0.69 (1.53) | BLZ-680 | BLZ-680/4 |
| 840 | 4.6 | 0.25 | 250 | 33.07 | 0.18 | 60 (132) | | 0.84 (1.86) | BLZ-840 | BLZ-840/4 |
| 1000 | 4.6 | 0.25 | 300 | 39.37 | 0.18 | 60 (132) | | 0.99 (2.18) | BLZ-1000 | BLZ-1000/4 |
| 200 | 7.9 | 0.25 | 50 | 7.87 | 0.31 | 170 (375) | | 0.47 (1.05) | BLHZ-200 | BLHZ-200/4 |
| 360 | 7.9 | 0.25 | 100 | 14.17 | 0.31 | 170 (375) | | 0.73 (1.60) | BLHZ-360 | BLHZ-360/4 |
| 520 | 7.9 | 0.25 | 150 | 20.47 | 0.31 | 170 (375) | | 0.98 (2.16) | BLHZ-520 | BLHZ-520/4 |
| 680 | 7.9 | 0.25 | 200 | 26.77 | 0.31 | 170 (375) | | 1.23 (2.72) | BLHZ-680 | BLHZ-680/4 |
| 840 | 7.9 | 0.25 | 250 | 33.07 | 0.31 | 170 (375) | | 1.48 (3.28) | BLHZ-840 | BLHZ-840/4 |
| 1000 | 7.9 | 0.25 | 300 | 39.37 | 0.31 | 170 (375) | | 1.74 (3.83) | BLHZ-1000 | BLHZ-1000/4 |