



Applications:

Suitable for corrosive climate condition, higher temperature and higher tensile strength requirement.


■ **Material:** Stainless Steel SS 316, SS 304

■ **Operating Temp:** -80°C to +150°C

■ **Unit:** 100 Pcs/Pkt

Features:

- Easy lock steel ties are self locking with multiple locking systems designed for fast, strong and secure Installation
- Coating material is non-toxic, halogen free, low smoke and UV resistant and provides long term life in corrosive climate



Length (mm)	Width (mm)	Thick (mm)	Max. Bun. Dia (mm)	Length (inch)	Width (inch)	Coating Type	Loop Ten. Str.		G.W. /100 pcs Kgs (lbs)	Cat No. SS 316	Cat No. SS 304
							Kgs	(Lbs)			
150	7.0	0.40	35	5.91	0.28	Polyster	45 (99)		0.24 (0.52)	EL-150CP	EL-150/4CP
150	7.0	0.40	35	5.91	0.28	Nylon	45 (99)		0.24 (0.52)	EL-150CN	EL-150/4CN
200	7.0	0.40	51	7.87	0.28	Polyster	45 (99)		0.31 (0.68)	EL-200CP	EL-200/4CP
200	7.0	0.40	51	7.87	0.28	Nylon	45 (99)		0.31 (0.68)	EL-200CN	EL-200/4CN
225	7.0	0.40	60	8.86	0.28	Polyster	45 (99)		0.33 (0.72)	EL-225CP	EL-225/4CP
225	7.0	0.40	60	8.86	0.28	Nylon	45 (99)		0.33 (0.72)	EL-225CN	EL-225/4CN
250	7.0	0.40	65	9.84	0.28	Polyster	45 (99)		0.35 (0.77)	EL-250CP	EL-250/4CP
250	7.0	0.40	65	9.84	0.28	Nylon	45 (99)		0.35 (0.77)	EL-250CN	EL-250/4CN
300	7.0	0.40	80	11.81	0.28	Polyster	45 (99)		0.44 (0.96)	EL-300CP	EL-300/4CP
300	7.0	0.40	80	11.81	0.28	Nylon	45 (99)		0.44 (0.96)	EL-300CN	EL-300/4CN
360	7.0	0.40	100	14.17	0.28	Polyster	45 (99)		0.51 (1.12)	EL-360CP	EL-360/4CP
360	7.0	0.40	100	14.17	0.28	Nylon	45 (99)		0.51 (1.12)	EL-360CN	EL-360/4CN
450	7.0	0.40	125	17.72	0.28	Polyster	45 (99)		0.61 (1.34)	EL-450CP	EL-450/4CP
450	7.0	0.40	125	17.72	0.28	Nylon	45 (99)		0.61 (1.34)	EL-450CN	EL-450/4CN
600	7.0	0.40	175	23.62	0.28	Polyster	45 (99)		0.79 (1.74)	EL-600CP	EL-600/4CP
600	7.0	0.40	175	23.62	0.28	Nylon	45 (99)		0.79 (1.74)	EL-600CN	EL-600/4CN
610	7.0	0.40	180	24.02	0.28	Polyster	45 (99)		0.83 (1.82)	EL-610CP	EL-610/4CP
610	7.0	0.40	180	24.02	0.28	Nylon	45 (99)		0.83 (1.82)	EL-610CN	EL-610/4CN
750	7.0	0.40	225	29.53	0.28	Polyster	45 (99)		1.01 (2.22)	EL-750CP	EL-750/4CP
750	7.0	0.40	225	29.53	0.28	Nylon	45 (99)		1.01 (2.22)	EL-750CN	EL-750/4CN
1000	7.0	0.40	300	39.37	0.28	Polyster	45 (99)		1.28 (2.82)	EL-1000CP	EL-1000/4CP
1000	7.0	0.40	300	39.37	0.28	Nylon	45 (99)		1.28 (2.82)	EL-1000CN	EL-1000/4CN
150	12.0	0.40	35	5.91	0.47	Polyster	111 (245)		0.47 (1.03)	ELH-150CP	ELH-150/4CP
150	12.0	0.40	35	5.91	0.47	Nylon	111 (245)		0.47 (1.03)	ELH-150CN	ELH-150/4CN
200	12.0	0.40	51	7.87	0.47	Polyster	111 (245)		0.62 (1.36)	ELH-200CP	ELH-200/4CP
200	12.0	0.40	51	7.87	0.47	Nylon	111 (245)		0.62 (1.36)	ELH-200CN	ELH-200/4CN
225	12.0	0.40	60	8.86	0.47	Polyster	111 (245)		0.66 (1.45)	ELH-225CP	ELH-225/4CP
225	12.0	0.40	60	8.86	0.47	Nylon	111 (245)		0.66 (1.45)	ELH-225CN	ELH-225/4CN
250	12.0	0.40	65	9.84	0.47	Polyster	111 (245)		0.72 (1.58)	ELH-250CP	ELH-250/4CP
250	12.0	0.40	65	9.84	0.47	Nylon	111 (245)		0.72 (1.58)	ELH-250CN	ELH-250/4CN
300	12.0	0.40	80	11.81	0.47	Polyster	111 (245)		0.84 (1.85)	ELH-300CP	ELH-300/4CP
300	12.0	0.40	80	11.81	0.47	Nylon	111 (245)		0.84 (1.85)	ELH-300CN	ELH-300/4CN



EASY LOCK STEEL TIE COATED



Stainless Steel Ties

Length (mm)	Width (mm)	Thick (mm)	Max. Bun. Dia (mm)	Length (inch)	Width (inch)	Coating Type	Loop Ten. Str.		G.W. /100 pcs Kgs (lbs)	Cat No. SS 316	Cat No. SS 304
							Kgs	(Lbs)			
360	12.0	0.40	100	14.17	0.47	Polyster	111	(245)	1.00 (2.20)	ELH-360CP	ELH-360/4CP
360	12.0	0.40	100	14.17	0.47	Nylon	111	(245)	1.00 (2.20)	ELH-360CN	ELH-360/4CN
450	12.0	0.40	125	17.72	0.47	Polyster	111	(245)	1.12 (2.46)	ELH-450CP	ELH-450/4CP
450	12.0	0.40	125	17.72	0.47	Nylon	111	(245)	1.12 (2.46)	ELH-450CN	ELH-450/4CN
600	12.0	0.40	175	23.62	0.47	Polyster	111	(245)	1.51 (3.32)	ELH-600CP	ELH-600/4CP
600	12.0	0.40	175	23.62	0.47	Nylon	111	(245)	1.51 (3.32)	ELH-600CN	ELH-600/4CN
610	12.0	0.40	180	24.02	0.47	Polyster	111	(245)	1.52 (3.35)	ELH-610CP	ELH-610/4CP
610	12.0	0.40	180	24.02	0.47	Nylon	111	(245)	1.52 (3.35)	ELH-610CN	ELH-610/4CN
750	12.0	0.40	225	29.53	0.47	Polyster	111	(245)	1.85 (4.07)	ELH-750CP	ELH-750/4CP
750	12.0	0.40	225	29.53	0.47	Nylon	111	(245)	1.85 (4.07)	ELH-750CN	ELH-750/4CN
1000	12.0	0.40	300	39.37	0.47	Polyster	111	(245)	2.48 (5.46)	ELH-1000CP	ELH-1000/4CP
1000	12.0	0.40	300	39.37	0.47	Nylon	111	(245)	2.48 (5.46)	ELH-1000CN	ELH-1000/4CN