



■ Applications:

- For cable bunching requirement in high temperature condition
- For durable locking in the adverse conditions like humidity, heat, cold, vibration & external shocks

- **Material:** Nylon 6.6
- **Color:** Light Green
- **Operating Temp:** -40°C to +125°C
- **Unit:** 100 Pcs/Pkt

Features:

- For wire/cable bunching in extreme temp. conditions of +125°C
- The corrosion proof, non-magnetic steel tooth firmly anchor inside the cable tie length (body) with positive locking.
- No chances of slippage in adverse conditions

Length (mm)	Width (mm)	Length (inch)	Ten. Str.		Max. Bun. Dia (mm)	Cat No.
			Kgs	Lbs		
100	2.5	4.0	8	18	22	SLM-100 /H
200	2.5	8.0	8	18	50	SLM-200 /H
150	3.6	6.0	18	40	30	SLM-150 I/H
200	3.6	8.0	18	40	50	SLM-200 I/H
280	3.6	11.0	18	40	76	SLM-280 I/H
200	4.8	8.0	22	49	50	SLM-200 S/H
290	4.8	11.4	22	49	78	SLM-290 S/H
360	4.8	14.2	22	49	102	SLM-360 S/H
220	7.6	8.6	54	119	57	SLM-220 LH/H
300	7.6	11.8	54	119	80	SLM-300 LH/H
368	7.6	14.5	54	119	102	SLM-368 LH/H
538	7.6	21.2	54	119	158	SLM-538 LH/H
780	7.6	30.7	54	119	230	SLM-780 LH/H

* Tolerance Dimension (mm):- Length - ± 4 , Width - ± 0.4 , Thickness - ± 0.4