



Applications:

Push mount ties are used to attach a bundle to another surface such as chassis of vehicles, Ac's, coolers (white goods). Used for harness assembly where there is constant vibration

- **Material:** Nylon 66
- **Color:** Natural / Black
- **Operating Temp:** -40°C to +85°C
- **Unit:** 100 Pcs/Pkt

Features:

- Quick and simple cable mounting
- Its one piece construction design eliminates the use of screw or adhesive mounts which holds the bundles on chassis
- Push mount tie head can be easily pressed into pre-drilled hole and can hold wire bunch
- Thumb release button allows to open wire bundles when changes are required

Length (mm)	Width (mm)	Length (inch)	Ten. Str.		Max. Bun. Dia (mm)	For Hole Dia (mm)	Cat No. Natural	Cat No. Black
			Kgs	Lbs				
150	7.0	5.9	22	49	32	6.0	SLRP-150 LH	SLRP-150 LH/B
200	7.0	7.9	22	49	50	6.0	SLRP-200 LH	SLRP-200 LH/B
250	7.5	9.9	22	49	65	6.0	SLRP-250 LH	SLRP-250 LH/B
300	7.5	11.8	22	49	80	6.0	SLRP-300 LH	SLRP-300 LH/B
380	7.5	15.0	22	49	105	6.0	SLRP-380 LH	SLRP-380 LH/B

* Tolerance Dimension (mm):- Length - ± 3 , Width - ± 0.1 , Thickness - ± 0.1 , For Hole Dia - ± 0.5