



■ **Applications:**

Suitable for corrosive climate condition, higher temperature and higher tensile strength requirement.

■ **Material:** Stainless Steel SS 316, SS 304

■ **Operating Temp:** -80°C to +538°C

■ **Unit:** 100 Pcs/Pkt

Features:

- Multi lock steel ties are self locking with multiple locking systems designed for strong and secure hold
- It is designed to accommodate double wraps
- Smooth edges of ties provide utmost safety while installation

Length (mm)	Width (mm)	Thick (mm)	Max. Bun. Dia (mm)	Length (inch)	Width (inch)	Loop Ten. Str.		G.W. /100 pcs Kgs (lbs)	Cat No. SS 316	Cat No. SS 304
						Kgs	(Lbs)			
150	7.0	0.25	35	5.91	0.28	60 (132)		0.26 (0.57)	ML-150	ML-150/4
225	7.0	0.25	60	8.86	0.28	60 (132)		0.33 (0.72)	ML-225	ML-225/4
300	7.0	0.25	80	11.81	0.28	60 (132)		0.42 (0.92)	ML-300	ML-300/4
450	7.0	0.25	125	17.72	0.28	60 (132)		0.59 (1.30)	ML-450	ML-450/4
610	7.0	0.25	180	24.02	0.28	60 (132)		0.78 (1.71)	ML-610	ML-610/4
150	12.0	0.25	35	5.91	0.47	130 (287)		0.45 (0.99)	MLH-150	MLH-150/4
225	12.0	0.25	60	8.86	0.47	130 (287)		0.59 (1.30)	MLH-225	MLH-225/4
300	12.0	0.25	80	11.81	0.47	130 (287)		0.76 (1.67)	MLH-300	MLH-300/4
450	12.0	0.25	125	17.72	0.47	130 (287)		1.07 (2.35)	MLH-450	MLH-450/4
610	12.0	0.25	180	24.02	0.47	130 (287)		1.49 (3.28)	MLH-610	MLH-610/4