



Applications:

For cable bunching in outdoor weather resistant application

- **Material:** Nylon 66
- **Color:** Black
- **Operating Temp:** -40°C to +85°C
- **Unit:** 100 Pcs/Pkt & 1000 Pcs/K

Features:

- Low cost, economical design & uncompromised tensile strength
- UV ties are produced from a special grade of UV resistant nylon 6.6 which gives longer years of life span in outdoor climatic condition

Length (mm)	Width (mm)	Length (inch)	Ten. Str.		Max. Bun. Dia (mm)	Cat No. 100 pcs pack (PKT)	Cat No. 1000 pcs pack (K)
			Kgs	Lbs			
100	2.2	3.9	8	18	22	SLV-100/U	SLV-100 K/U
150	3.2	5.9	18	40	35	SLV-150 I/U	SLV-150 IK/U
200	3.2	7.9	18	40	50	SLV-200 I/U	SLV-200 IK/U
200	4.2	7.9	22	49	50	SLV-200 S/U	SLV-200 SK/U
250	4.2	9.8	22	49	65	SLV-250 S/U	
300	4.2	11.8	22	49	82	SLV-300 S/U	
355	4.2	14.0	22	49	100	SLV-355 S/U	
200	7.0	7.9	54	119	50	SLV-200 LH/U	
250	7.0	9.8	54	119	65	SLV-250 LH/U	
300	7.0	11.8	54	119	82	SLV-300 LH/U	
350	7.0	13.8	54	119	100	SLV-350 LH/U	
380	7.0	15.0	54	119	108	SLV-380 LH/U	
400	7.0	15.7	54	119	110	SLV-400 LH/U	
450	7.0	17.7	54	119	130	SLV-450 LH/U	
500	7.0	19.7	54	119	148	SLV-500 LH/U	
600	7.0	23.6	54	119	180	SLV-600 LH/U	

* Tolerance Dimension (mm):- Length - ± 1 to 3, Width - ± 0.1 to 0.2, Thickness - ± 0.05 to 0.1