



### Applications:

Most versatile clamp to hold cable, tubes, components

- **Material:** Nylon 6: UL 94 V-2
- **Color:** Natural
- **Operating Temp:** -40°C to +85°C
- **Unit:** 100 Pcs/Pkt

### Features:

- Offer fix & adjustable design for various wire/cable diameter
- Easy mounting with screw

Size No.	Suitable Wire O.D. A (inch/mm)	Length L (mm)	Width W (mm)	Mounting Hole $\phi$ Dia (mm)	Cat No. Natural
No.0 Fix	1/8 (3.0)	13.45	6.05	4.00	PC-3
No.00 "	3/16 (4.5)	17.20	7.40	3.80	PC-4
No.1 "	1/4 (6.0)	18.30	8.30	4.05	PC-6
No.2 "	5/16 (7.5)	22.10	9.55	4.15	PC-7
No.3 "	3/8 (9.0)	23.45	9.65	4.40	PC-9
No.4 "	7/16 (10.0)	25.15	9.70	4.50	PC-10
No.5 "	1/2 (12.5)	28.70	11.35	4.30	PC-12
No.5A "	5/8 (15.0)	32.35	11.00	4.40	PC-15
No.6A "	3/4 (19.0)	38.50	12.05	5.20	PC-19
No.10A "	1 (25.0)	45.20	13.00	5.15	PC-25
No.000 Adjustable	1/4 (4.5 to 7)	21 to 16	6.40	3.00	PC-7 A
No.6 "	7/8 (15 to 22)	52 to 42	13.00	5.05	PC-22 A
No.7 "	1 1/4 (22 to 30)	62 to 52	12.95	5.30	PC-30 A
No.8 "	1 1/2 (30 to 38)	73 to 62	14.00	5.80	PC-38 A
No.9 "	1 3/4 (38 to 46)	84 to 72	14.00	5.55	PC-46 A

\* Tolerance Dimension (mm):- Length -  $\pm 1$ , Width -  $\pm 1$ , Thickness -  $\pm 0.5$ , Hole -  $\pm 1$