



Applications:

For indoor / outdoor wire cable bunching. Outside serration ties minimize the damage to the surface of the strapped object or cable insulation

- **Material:** Nylon 66
- **Color:** Black
- **Operating Temp:** -40°C to +85°C
- **Unit:** 100 Pcs/Pkt

Features:

- Cable tie is an economical & versatile method of cable/wire bunching systems
- Cable tie has self-locking & one-piece construction which ensure the fast & easy installation
- Non-releasable cable tie, once locked cannot be opened or reused

Length (mm)	Width (mm)	Thick (mm)	Length (inch)	Ten. Str.		Bundle Ø (mm)	Cat No. Natural	Cat No. Black	Cat No. UV	Cat No. Heat Stabilised Black
				Kgs	Lbs					
100	2.5	0.97	3.94	8	18	22	ATOS-100	ATOS-100B	ATOS-100U	ATOS-100HB
200	3.6	1.15	7.87	18	40	54	ATOS-200I	ATOS-200IB	ATOS-200IU	ATOS-200IHB
150	4.7	1.35	5.90	22	49	40	ATOS-150S	ATOS-150SB	ATOS-150SU	ATOS-150SHB
200	4.7	1.35	7.87	22	49	54	ATOS-200S	ATOS-200SB	ATOS-200SU	ATOS-200SHB
384	4.7	1.35	15.12	22	49	114	ATOS-384S	ATOS-384SB	ATOS-384SU	ATOS-384SHB
380	7.6	1.76	14.96	55	121	112	ATOS-380LH	ATOS-380LHB	ATOS-380LHU	ATOS-380LHHB

* Tolerance Dimension (mm):- Length - ± 2 , Width - ± 0.2 , Thickness - ± 0.2