



Applications:

For fixing cable harness in automotive industries. Also used in aviation, white goods manufacturing & panel building

- **Material:** Nylon 66
- **Color:** Black
- **Operating Temp:** -40°C to +85°C
- **Unit:** 100 Pcs/Pkt

Features:

- FIR tree tie with disc secures wire harness firmly & minimize access of dust and water
- It is suitable to a varied thickness of chassis or one side thread hole

Length (mm)	Width (mm)	Thick (mm)	Length (inch)	Ten. Str.		Max. Bundle Ø (mm)	FIR Ø (mm)	Suitable for Hole Ø (mm)	Panel Thick (mm)	Disc Ø (mm)	Cat No. Black
				Kgs	Lbs						
161	4.7	1.35	6.33	22	49	38	9.1	8.0 - 8.5	0.6 - 6.0	16	ATPF-1617S/B
162	4.7	1.35	6.37	22	49	38	9.1	8.0 - 8.5	0.7 - 7.0	16	ATPF-1628S/B
165	4.7	1.35	6.49	22	49	38	7.5	6.3 - 7.0	0.7 - 7.0	16	ATPF-1657S/B

* Tolerance Dimension (mm):- Length - ± 3 , Width - ± 0.2 , Thickness - ± 0.2 , FIR Dia - ± 2 , Suitable for Hole Dia - ± 0.5