



■ Applications:

Suitable for corrosive climate condition, higher temperature and higher tensile strength requirement.

■ **Material:** Stainless Steel SS 316, SS 304

■ **Operating Temp:** -80°C to +150°C

■ **Unit:** 100 Pcs/Pkt

Features:

- Designed for low cost & low tensile applications
- Smooth edges of ties provide utmost safety while installation
- Coating material is Non-toxic, halogen free, low smoke and UV resistant with long term life in corrosive climate

Length (mm)	Width (mm)	Thick (mm)	Max. Bun. Dia (mm)	Length (inch)	Width (inch)	Coating Type	Loop Ten. Str.		G.W. /100 pcs Kgs (lbs)	Cat No. SS 316	Cat No. SS 304
							Kgs	(Lbs)			
150	5.0	0.70	30	5.91	0.20	Polyester	120	(264)	0.41 (0.90)	RTE-150CP	RTE-150/4CP
150	5.0	1.10	30	5.91	0.20	Thermoplastics	120	(264)	0.42 (0.92)	RTE-150CT	RTE-150/4CT
150	5.0	0.70	30	5.91	0.20	Nylon	120	(264)	0.41 (0.90)	RTE-150CN	RTE-150/4CN
230	5.0	0.70	54	9.06	0.20	Polyester	120	(264)	0.59 (1.30)	RTE-230CP	RTE-230/4CP
230	5.0	1.10	54	9.06	0.20	Thermoplastics	120	(264)	0.60 (1.32)	RTE-230CT	RTE-230/4CT
230	5.0	0.70	54	9.06	0.20	Nylon	120	(264)	0.59 (1.30)	RTE-230CN	RTE-230/4CN
330	5.0	0.70	85	12.99	0.20	Polyester	120	(264)	0.81 (1.78)	RTE-330CP	RTE-330/4CP
330	5.0	1.10	85	12.99	0.20	Thermoplastics	120	(264)	0.82 (1.80)	RTE-330CT	RTE-330/4CT
330	5.0	0.70	85	12.99	0.20	Nylon	120	(264)	0.81 (1.78)	RTE-330CN	RTE-330/4CN
450	5.0	0.70	125	17.72	0.20	Polyester	120	(264)	1.07 (2.35)	RTE-450CP	RTE-450/4CP
450	5.0	1.10	125	17.72	0.20	Thermoplastics	120	(264)	1.08 (2.38)	RTE-450CT	RTE-450/4CT
450	5.0	0.70	125	17.72	0.20	Nylon	120	(264)	1.07 (2.35)	RTE-450CN	RTE-450/4CN
610	5.0	0.70	175	24.02	0.20	Polyester	120	(264)	1.42 (3.13)	RTE-610CP	RTE-610/4CP
610	5.0	1.10	175	24.02	0.20	Thermoplastics	120	(264)	1.44 (3.17)	RTE-610CT	RTE-610/4CT
610	5.0	0.70	175	24.02	0.20	Nylon	120	(264)	1.42 (3.13)	RTE-610CN	RTE-610/4CN
762	5.0	0.70	220	30.00	0.20	Polyester	120	(264)	1.75 (3.85)	RTE-762CP	RTE-762/4CP
762	5.0	1.10	220	30.00	0.20	Thermoplastics	120	(264)	1.77 (3.90)	RTE-762CT	RTE-762/4CT
762	5.0	0.70	220	30.00	0.20	Nylon	120	(264)	1.75 (3.85)	RTE-762CN	RTE-762/4CN
914	5.0	0.70	270	35.98	0.20	Polyester	120	(264)	2.08 (4.58)	RTE-914CP	RTE-914/4CP
914	5.0	1.10	270	35.98	0.20	Thermoplastics	120	(264)	2.10 (4.62)	RTE-914CT	RTE-914/4CT
914	5.0	0.70	270	35.98	0.20	Nylon	120	(264)	2.08 (4.58)	RTE-914CN	RTE-914/4CN