



■ Applications:

Suitable for corrosive climate condition, higher temperature and higher tensile strength requirement.

■ **Material:** Stainless Steel SS 316, SS 304

■ **Operating Temp:** -80°C to +150°C

■ **Unit:** 100 Pcs/Pkt

Features:

- Reusable steel ties are designed for quick fastening of cables, tubes, pipes etc. & also can be unfastened for reuse
- It is designed to accommodate double wraps.
- Coating material is non-toxic, halogen free, low smoke and UV resistant and provides long term life in corrosive climate

Length (mm)	Width (mm)	Thick (mm)	Max. Bun. Dia (mm)	Length (inch)	Width (inch)	Coating Type	Loop Ten. Str.		G.W. /100 pcs Kgs (lbs)	Cat No. SS 316	Cat No. SS 304
							Kgs	(Lbs)			
152	6.3	0.70	32	5.98	0.25	Polyster	149	(322)	0.58 (1.27)	RT-152CP	RT-152/4CP
152	6.3	1.1	32	5.98	0.25	Thermoplastic	149	(322)	0.60 (1.32)	RT-152CT	RT-152/4CT
152	6.3	0.70	32	5.98	0.25	Nylon	149	(322)	0.58 (1.27)	RT-152CN	RT-152/4CN
229	6.3	0.70	57	9.02	0.25	Polyster	149	(322)	0.80 (1.76)	RT-229CP	RT-229/4CP
229	6.3	1.1	57	9.02	0.25	Thermoplastic	149	(322)	0.82 (1.80)	RT-229CT	RT-229/4CT
229	6.3	0.70	57	9.02	0.25	Nylon	149	(322)	0.80 (1.76)	RT-229CN	RT-229/4CN
305	6.3	0.70	81	12.01	0.25	Polyster	149	(322)	0.98 (2.16)	RT-305CP	RT-305/4CP
305	6.3	1.1	81	12.01	0.25	Thermoplastic	149	(322)	1.01 (2.22)	RT-305CT	RT-305/4CT
305	6.3	0.70	81	12.01	0.25	Nylon	149	(322)	0.98 (2.16)	RT-305CN	RT-305/4CN
457	6.3	0.70	130	17.99	0.25	Polyster	149	(322)	1.38 (3.04)	RT-457CP	RT-457/4CP
457	6.3	1.1	130	17.99	0.25	Thermoplastic	149	(322)	1.41 (3.10)	RT-457CT	RT-457/4CT
457	6.3	0.70	130	17.99	0.25	Nylon	149	(322)	1.38 (3.04)	RT-457CN	RT-457/4CN
500	6.3	0.70	143	19.69	0.25	Polyster	149	(322)	1.66 (3.65)	RT-500CP	RT-500/4CP
500	6.3	1.1	143	19.69	0.25	Thermoplastic	149	(322)	1.71 (3.76)	RT-500CT	RT-500/4CT
500	6.3	0.70	143	19.69	0.25	Nylon	149	(322)	1.66 (3.65)	RT-500CN	RT-500/4CN
610	6.3	0.70	178	24.02	0.25	Polyster	149	(322)	1.84 (4.05)	RT-610CP	RT-610/4CP
610	6.3	1.1	178	24.02	0.25	Thermoplastic	149	(322)	1.89 (4.16)	RT-610CT	RT-610/4CT
610	6.3	0.70	178	24.02	0.25	Nylon	149	(322)	1.84 (4.05)	RT-610CN	RT-610/4CN
152	9.5	0.70	32	5.98	0.37	Polyster	181	(399)	0.90 (1.98)	RTH-152CP	RTH-152/4CP
152	9.5	1.1	32	5.98	0.37	Thermoplastic	181	(399)	0.93 (2.05)	RTH-152CT	RTH-152/4CT
152	9.5	0.70	32	5.98	0.37	Nylon	181	(399)	0.90 (1.98)	RTH-152CN	RTH-152/4CN
229	9.5	0.70	57	9.02	0.37	Polyster	181	(399)	1.20 (2.64)	RTH-229CP	RTH-229/4CP
229	9.5	1.1	57	9.02	0.37	Thermoplastic	181	(399)	1.24 (2.73)	RTH-229CT	RTH-229/4CT
229	9.5	0.70	57	9.02	0.37	Nylon	181	(399)	1.20 (2.64)	RTH-229CN	RTH-229/4CN
305	9.5	0.70	81	12.01	0.37	Polyster	181	(399)	1.50 (3.30)	RTH-305CP	RTH-305/4CP
305	9.5	1.1	81	12.01	0.37	Thermoplastic	181	(399)	1.55 (3.41)	RTH-305CT	RTH-305/4CT
305	9.5	0.70	81	12.01	0.37	Nylon	181	(399)	1.50 (3.30)	RTH-305CN	RTH-305/4CN
457	9.5	0.70	130	17.99	0.37	Polyster	181	(399)	2.08 (4.25)	RTH-457CP	RTH-457/4CP
457	9.5	1.1	130	17.99	0.37	Thermoplastic	181	(399)	2.14 (4.71)	RTH-457CT	RTH-457/4CT
457	9.5	0.70	130	17.99	0.37	Nylon	181	(399)	2.08 (4.25)	RTH-457CN	RTH-457/4CN
500	9.5	0.70	143	19.69	0.37	Polyster	181	(399)	2.19 (4.82)	RTH-500CP	RTH-500/4CP
500	9.5	1.1	143	19.69	0.37	Thermoplastic	181	(399)	2.25 (4.96)	RTH-500CT	RTH-500/4CT



REUSABLE STEEL TIE COATED



Stainless Steel Ties

Length (mm)	Width (mm)	Thick (mm)	Max. Bun. Dia (mm)	Length (inch)	Width (inch)	Coating Type	Loop Ten. Str.		G.W. /100 pcs Kgs (lbs)	Cat No. SS 316	Cat No. SS 304
							Kgs	(Lbs)			
500	9.5	0.70	143	19.69	0.37	Nylon	181	(399)	2.19 (4.82)	RTH-500CN	RTH-500/4CN
610	9.5	0.70	178	24.02	0.37	Polyster	181	(399)	2.60 (5.73)	RTH-610CP	RTH-610/4CP
610	9.5	1.1	178	24.02	0.37	Thermoplastic	181	(399)	2.67 (5.88)	RTH-610CT	RTH-610/4CT
610	9.5	0.70	178	24.02	0.37	Nylon	181	(399)	2.60 (5.73)	RTH-610CN	RTH-610/4CN
762	9.5	0.70	227	30.00	0.37	Polyster	181	(399)	3.35 (7.38)	RTH-762CP	RTH-762/4CP
762	9.5	1.1	227	30.00	0.37	Thermoplastic	181	(399)	3.45 (7.60)	RTH-762CT	RTH-762/4CT
762	9.5	0.70	227	30.00	0.37	Nylon	181	(399)	3.35 (7.38)	RTH-762CN	RTH-762/4CN
914	9.5	0.70	275	35.98	0.37	Polyster	181	(399)	3.72 (8.20)	RTH-914CP	RTH-914/4CP
914	9.5	1.1	275	35.98	0.37	Thermoplastic	181	(399)	3.82 (8.42)	RTH-914CT	RTH-914/4CT
914	9.5	0.70	275	35.98	0.37	Nylon	181	(399)	3.72 (8.20)	RTH-914CN	RTH-914/4CN