



#### ■ Applications:

Suitable for corrosive climate condition, higher temperature and higher tensile strength requirement.

■ **Material:** Stainless Steel SS 316, SS 304

■ **Operating Temp:** -80°C to +538°C

■ **Unit:** 100 Pcs/Pkt

#### Features:

- Reusable steel ties are designed for quick fastening of cables, tubes, pipes etc. & also can be unfastened for reuse
- It is designed to accommodate double wraps
- Smooth edges of ties provide utmost safety while installation.

| Length (mm) | Width (mm) | Thick (mm) | Max. Bun. Dia (mm) | Length (inch) | Width (inch) | Loop Ten. Str. |       | G.W. /100 pcs Kgs (lbs) | Cat No. SS 316 | Cat No. SS 304 |
|-------------|------------|------------|--------------------|---------------|--------------|----------------|-------|-------------------------|----------------|----------------|
|             |            |            |                    |               |              | Kgs            | (Lbs) |                         |                |                |
| 152         | 6.3        | 0.50       | 32                 | 5.98          | 0.25         | 149(322)       |       | 0.55 (1.21)             | RT-152         | RT-152/4       |
| 229         | 6.3        | 0.50       | 57                 | 9.02          | 0.25         | 149(322)       |       | 0.75 (1.65)             | RT-229         | RT-229/4       |
| 305         | 6.3        | 0.50       | 81                 | 12.01         | 0.25         | 149(322)       |       | 0.92 (2.02)             | RT-305         | RT-305/4       |
| 457         | 6.3        | 0.50       | 130                | 17.99         | 0.25         | 149(322)       |       | 1.29 (2.84)             | RT-457         | RT-457/4       |
| 500         | 6.3        | 0.50       | 143                | 19.69         | 0.25         | 149(322)       |       | 1.56 (3.43)             | RT-500         | RT-500/4       |
| 610         | 6.3        | 0.50       | 178                | 24.02         | 0.25         | 149(322)       |       | 1.72 (3.79)             | RT-610         | RT-610/4       |
| 152         | 9.5        | 0.50       | 32                 | 5.98          | 0.37         | 181(399)       |       | 0.85 (1.87)             | RTH-152        | RTH-152/4      |
| 229         | 9.5        | 0.50       | 57                 | 9.02          | 0.37         | 181(399)       |       | 1.13 (2.49)             | RTH-229        | RTH-229/4      |
| 305         | 9.5        | 0.50       | 81                 | 12.01         | 0.37         | 181(399)       |       | 1.41 (3.10)             | RTH-305        | RTH-305/4      |
| 457         | 9.5        | 0.50       | 130                | 17.99         | 0.37         | 181(399)       |       | 1.95 (4.29)             | RTH-457        | RTH-457/4      |
| 500         | 9.5        | 0.50       | 143                | 19.69         | 0.37         | 181(399)       |       | 2.05 (4.52)             | RTH-500        | RTH-500/4      |
| 610         | 9.5        | 0.50       | 178                | 24.02         | 0.37         | 181(399)       |       | 2.43 (5.35)             | RTH-610        | RTH-610/4      |
| 762         | 9.5        | 0.50       | 227                | 30.00         | 0.37         | 181(399)       |       | 3.14 (6.92)             | RTH-762        | RTH-762/4      |
| 914         | 9.5        | 0.50       | 275                | 35.98         | 0.37         | 181(399)       |       | 3.48 (7.67)             | RTH-914        | RTH-914/4      |