

Applications:

For supporting & holding cable / wire bunch

Material:

Nylon 6: UL 94 V-2 (backed with double sided rubber adhesive tape)

Color:

Natural

Operating Temp:




-29°C to +49°C (Max. Intermittent Temp. I.e. less than 2 hrs. 70°C)

Unit:


100 Pcs/Pkt

Features:

- Curved walls allow the wire bundles to seat firmly in position after Installing with cable ties
- Rubber based closed cell foam adhesive is used for better surface adhesion
- Design to support light weight wire bundles



TM-12
TM-19
TM-26



Size (mm)	Length L (mm)	Width W (mm)	Height H (mm)	Slot L x H (mm)	For Cable Tie Width (mm)	Cat. No. Natural
12 x 12	12.5	12.5	6.0	2.8 x 1.5	2.5	TM-12
19 x 19	19.0	19.0	6.5	4.5 x 1.3	3.6	TM-19
26 x 26	26.0	26.0	6.8	6.2 x 1.4	4.8	TM-26
38 x 38	38.0	38.0	8.5	7.8 x 1.5	4.8	TM-38
50 x 50	50.5	50.5	9.0	8.0 x 2.0	7.8	TM-50

* Tolerance Dimension (mm):- Length - ± 1 , Width - ± 1 , Height - ± 0.5 , Slot - ± 1