



Applications:

Cable identification in corrosive climatic condition

■ **Material:** Stainless Steel SS 316

■ **Operating Temp:** -80°C to +538°C

■ **Unit:** 100 Pcs/Pkt

Features:

- The unique slide - on design enables quick & easy assembly by using multi lock, easy lock & ball lock steel ties. (Available in different length with screw mounting hole \varnothing 3 m).
- Slide - on premarked marker strip is required to be slided inside the carrier rails & break - off from the precut divisions with thumb pressure as per the marking requirement.
- Slide - on marker strips are available in alphabets, numbers & symbols like (0 to 9 / A to Z / +, -, /, ., Blank, \pm)

Length (mm)	Length (inch)	Width (mm)	Mounting Hole Centers (mm)	Accommodates Max. No. of Markers/Rail (Pcs.)	G.W. /100 pcs Kgs (lbs)	Cat No. SS 316	Cat No. SS 304
46	1.81	11	11	5	0.14 (0.30)	SCR-46	SCR-46/4
56	2.20	11	21	6	0.17 (0.37)	SCR-56	SCR-56/4
82	3.23	11	47	11	0.26 (0.57)	SCR-82	SCR-82/4
106	4.17	11	71	15	0.34 (0.75)	SCR-106	SCR-106/4
286	11.26	11	250	44	0.92 (2.02)	SCR-286	SCR-286/4

Slide on Marker for Carrier Rails

Description	Std. Qty./Bag	G.W. /100 pcs Kgs (lbs)	Cat No.
Slide-on marker strips character height 10mm (while ordering just mention the alphabet, Number or Symbol in bracket along with the Cat. No.)i.e. For example SMS(6), SMS(+) etc.	10 Markers/Strip & 10 Strips/Bag (Total 100 Markers)/Bag	0.026 (0.058)	SMS