



■ Applications:

Abrasion protection of wire & cable insulation & hydraulic or pneumatic tubing

- **Material:** P.E.
- **Color:** Natural, Black
- **Operating Temp:** -40°C to +85°C
- **Packing:** 50 Mtrs., 25 Mtrs., 10 Mtrs. Roll

Features:

- Can reuse when the change are required in bundle
- Can use in gapped manner where flexibility, breakouts & economy is required
- Can use in butted manner where rigidity & protection is required against continuously abrasion

Size	ID (mm)	OD (mm)	Pitch B (mm)	Thick (mm)	Bun. Range (mm)	Std Qty/Roll	Cat No.
1/8"	2.1	3.2	3.2	0.55	1.6 - 12.7	50 Mtrs.	ST-3
1/4"	4.8	6.3	6.3	0.75	4.8 - 40	50 Mtrs.	ST-6
3/8"	7.8	9.5	9.5	0.85	8.0 - 76	25 Mtrs.	ST-9
1/2"	10.5	12.7	12.7	1.1	19.1 - 102	25 Mtrs.	ST-12
5/8"	13.6	16.0	16.0	1.2	22 - 114	25 Mtrs.	ST-15
3/4"	16.4	19.0	19.0	1.3	25 - 127	25 Mtrs.	ST-19
1"	22.8	25.4	25.4	1.3	32 - 135	25 Mtrs.	ST-25
1 1/2"	34.10	38.1	38.1	2.0	43 - 170	10 Mtrs.	ST-38

* Tolerance Dimension (mm):- I D - ± 2 , O D - ± 2 , Pitch - ± 2 , Thickness - ± 0.2