



■ Applications:

Abrasion protection of wire & cable insulation & hydraulic or pneumatic tubing

- **Material:** P.E.
- **Color:** Natural, Black
- **Operating Temp:** -40°C to +85°C
- **Packing:** 50 Mtrs., 25 Mtrs., 10 Mtrs. Roll

Features:

- Can reuse when the change are required in bundle
- Can use in gapped manner where flexibility, breakouts & economy is required
- Can use in butted manner where rigidity & protection is required against continuously abrasion

Size	ID (mm)	OD (mm)	Pitch B (mm)	Thick (mm)	Bun. Range (mm)	Std Qty/Roll	Cat No.
1/4"	5.0	6.0	6.0	0.50	4.8 - 40	50 Mtrs.	ST-6L
3/8"	7.8	9.0	9.0	0.60	8.0 - 76	25 Mtrs.	ST-9L
1/2"	10.6	12.0	12.0	0.70	19.1 - 102	25 Mtrs.	ST-12L
5/8"	13.4	15.0	15.0	0.80	22 - 114	25 Mtrs.	ST-15L
3/4"	17.2	19.0	19.0	0.90	25 - 127	25 Mtrs.	ST-19L
1"	23.2	25.0	25.0	0.90	32 - 135	25 Mtrs.	ST-25L
1 1/2"	34.8	38.0	38.0	1.60	43 - 170	10 Mtrs.	ST-38L

* Tolerance Dimension (mm):- I D - ± 1 , O D - ± 1 , Pitch - ± 1 , Thickness - ± 0.2