



#### Applications:

Clamps hose, poles, pipes, cables etc.

- **Material:** SS 316
- **Operating Temp:** -80°C to +538°C
- **Packing:** 50 Pcs. Box

#### Features:

- Provides higher tensile strength
- Ideal for use in high vibration application
- Available in cardboard box as well as in plastic totes for easy to carry & use
- Smooth edges of band provide utmost safety while installation

Length		Width		Thickness mm	SS Grade	Max. Bun. Dia (mm)	Ten. Str.		Package Qty. per Box	G.W per 100 Pcs.		Cat No.
mm	inch	mm	inch				Kgs	Lbs		Kgs	(Lbs)	
305	12.7	12	1/2	0.38	SS 201	65	311	686	50 Pcs.	1.00 (2.20)	SBF-12300/1	
400	12.7	15 <sup>3/4</sup>	1/2	0.38	SS 201	89	311	686	50 Pcs.	1.21 (2.66)	SBF-12400/1	
495	12.7	19 <sup>1/2</sup>	1/2	0.38	SS 201	135	311	686	50 Pcs.	1.42 (3.13)	SBF-12500/1	
648	12.7	25 <sup>1/2</sup>	1/2	0.38	SS 201	165	311	686	50 Pcs.	1.75 (3.85)	SBF-12650/1	
851	12.7	33 <sup>1/2</sup>	1/2	0.38	SS 201	218	311	686	50 Pcs.	2.17 (4.78)	SBF-12850/1	
1041	12.7	41	1/2	0.38	SS 201	300	311	686	50 Pcs.	2.60 (5.73)	SBF-121050CP/1	
305	15.9	12	5/8	0.38	SS 316	65	340	750	50 Pcs.	1.32 (2.91)	SBF-15300	
305	15.9	12	5/8	0.38	SS 201	65	340	750	50 Pcs.	1.32 (2.91)	SBF-15300/1	
400	15.9	15 <sup>3/4</sup>	5/8	0.38	SS 316	89	340	750	50 Pcs.	1.58 (3.48)	SBF-15400	
400	15.9	15 <sup>3/4</sup>	5/8	0.38	SS 201	89	340	750	50 Pcs.	1.58 (3.48)	SBF-15400/1	
495	15.9	19 <sup>1/2</sup>	5/8	0.38	SS 316	135	340	750	50 Pcs.	1.85 (4.07)	SBF-15500	
495	15.9	19 <sup>1/2</sup>	5/8	0.38	SS 201	135	340	750	50 Pcs.	1.85 (4.07)	SBF-15500/1	
648	15.9	25 <sup>1/2</sup>	5/8	0.38	SS 316	165	340	750	50 Pcs.	2.25 (4.96)	SBF-15650	
648	15.9	25 <sup>1/2</sup>	5/8	0.38	SS 201	165	340	750	50 Pcs.	2.25 (4.96)	SBF-15650/1	
851	15.9	33 <sup>1/2</sup>	5/8	0.38	SS 316	218	340	750	50 Pcs.	2.78 (6.13)	SBF-15850	
851	15.9	33 <sup>1/2</sup>	5/8	0.38	SS 201	218	340	750	50 Pcs.	2.78 (6.13)	SBF-15850/1	
1041	15.9	41	5/8	0.38	SS 316	300	340	750	50 Pcs.	3.32 (7.32)	SBF-151050	
1041	15.9	41	5/8	0.38	SS 201	300	340	750	50 Pcs.	3.32 (7.32)	SBF-151050/1	
305	19.0	12	3/4	0.38	SS 201	65	408	900	25 Pcs.	1.43 (3.15)	SBF-19300/1	
400	19.0	15 <sup>3/4</sup>	3/4	0.38	SS 201	89	408	900	25 Pcs.	1.75 (3.85)	SBF-19400/1	
495	19.0	19 <sup>1/2</sup>	3/4	0.38	SS 201	135	408	900	25 Pcs.	2.07 (4.56)	SBF-19500/1	
648	19.0	25 <sup>1/2</sup>	3/4	0.38	SS 201	165	408	900	25 Pcs.	2.54 (5.6)	SBF-19650/1	
851	19.0	33 <sup>1/2</sup>	3/4	0.38	SS 201	218	408	900	25 Pcs.	3.18 (7.01)	SBF-19850/1	
1041	19.0	41	3/4	0.38	SS 201	300	408	900	25 Pcs.	3.82 (8.42)	SBF-191050/1	