



■ Applications:

Cable bundling application for higher tensile load and high vibration. For various size of cable diameter requirement.

- **Material:** SS 316
- **Operating Temp:** -80°C to +150°C
- **Coating:** Black PPA - Thermoplastic or Polyester
- **Packing:** 25 Mtrs (82.5 Ft.)/Roll in box

Features:

- Provides higher tensile strength
- Ideal for use in high vibration application
- Available in cardboard box as well as in plastic totes for easy to carry & use.
- Coating material is non-toxic, halogen free, low smoke and UV resistant with long term life in corrosive climate

Width		Thickness		SS Grade	Ten. Str.		Used with Buckle/Clip	Package Qty. per Box	G.wt./Std. Pkg		Cat No.
(inch)	(mm)	(inch)	(mm)		Kgs	Lbs			Kgs	Lbs	
1/4	6.3	0.048	1.22	SS 316	152	335	SBC-6	25 Mtrs (82.5 Ft.)	0.9	2.0	SBL-638CT
3/8	9.5	0.048	1.22	SS 316	228	503	SBC-9	25 Mtrs (82.5 Ft.)	1.2	2.6	SBL-938CT
1/2	12.7	0.048	1.22	SS 316	303	668	SBC-12	25 Mtrs (82.5 Ft.)	1.6	3.5	SBL-1238CT
5/8	15.9	0.048	1.22	SS 316	380	838	SBC-15	25 Mtrs (82.5 Ft.)	2.0	4.4	SBL-1538CT
3/4	19.0	0.048	1.22	SS 316	453	999	SBC-19	25 Mtrs (82.5 Ft.)	2.4	5.3	SBL-1938CT